

Material Safety Data Sheet

Product description

GB007 wallpaper glue GB007 is made of high quality modified starch with additives, as deionized water, anti-mildew, anti-corrosion and so on, possesses such features as natural eco-environmental product with strong stickiness, strong bonding strength, so it is widely used for bonding every kind of wallpaper glue.

Recommended use

It is suitable for bonding all kinds of wallpaper.

Product Data

Appearance	White liquid
Viscosity	glue:water=1:1 41000 mPa. S/20°C /humidity 67% glue:water=1:1.2 32000 mPa. S/20°C /humidity 67%
Odor	Starch odor
Solubility in water	Soluble in water
Bulk Density	Not available
Boiling point	Not available
Vapor Pressure	Not available
Melting Point:	Not available
Specific Gravity:	Not available
Ignition Temperature:	Not available

Application Tools

Clean bucket, water, brush, scraper, tape measure and paper knife.

1. Spread the wallpaper out on a flat surface, pour the mixed glue on the back of the wallpaper or on to Wall in a straight line, and then spread the glue evenly with a short-haired brush(1.5-3cm). The consumption of glue is about 100-120g/sqm.
2. Fold the wallpaper, keep still for 5-10 minutes, and then paste it on the wall
3. Press the paper with the scraper to force the excess glue and air out through the edges.
4. Use the scraper or a seam roller to press the seams tightly together.
5. Wipe off the excess glue with a wet towel.

Material Safety Data Sheet

Health Hazards Identification and Personal Protection

- Potential Health Effects:** Breathing dust may cause irritating to respiratory track. Repeated or prolonged contact may cause skin and eye
- Respiratory protection:** Paper or cloth mask recommended.
- Eye protection:** Safety glasses or other eye protection recommended.
- Skin protection:** Not required.
- Ventilation:** Handle in a manner that will minimize dusting.
-

First Aid Procedure

- Inhalation:** Move to fresh air
- Skin contact:** Wash with soap and water. Get medical attention if irritation develops.
- Eye contact:** Immediately flush eyes with water. Get medical attention if irritation
- Ingestion:** Wash out mouth with water. Call a doctor immediately if large quantities of this material are swallowed and feeling unwell.
-

Fire Fighting Media and Instruction

- Flammability of the Product:** Not combustible at high temperature
- Auto-Ignition Temperature:** Not available
- Flash point:** Not available
- Flammability Limits:** Not available
- Products of Combustion:** Carbon Monoxide, Carbon,Dioxide
- Fire Hazards in Presence of VariousSubstances:** Slightly flammable to flammable in presence of heat
- Small Fire: Use dry chemical powder.
- Large Fire: Use water spray, fog or foam, use water jet.
Self-contained breathing apparatus and full protective

Fire fighting instruction:

Special remarks on Fire Hazards Not available.

Explosion Hazard Data**Explosion Hazards in Presence of Various Substances:**

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Special remarks on Explosion Hazards: Not available

Accidental Release Measures

Material Safety Data Sheet

Wear appropriate personal protective equipments. Remove all source of ignition. Clean up spills in a manner that does not disperse dust into the air. Use non-sparking tools and equipment. Pick up spill

Attention:

1. Short-haired brush is strongly recommended.
2. More water can be added if the wallpaper is highly absorbent.
3. The average viscosity for wallpaper and wall cloth is more than 26 000mpa

▪ Handling and Storage

Handling: This product should be handled with the care.

Storage: Keep in tightly closed container, stored in a cool, dry and ventilated area. Do not store together with odorous or toxic substance.

Shelf Life 12 months in sealed

Packing size cans 20kg/tin

Distributor: Australia & New Zealand SDA 2/7 Neutron Place Rowville Vic. 3178 Australia

